

Tabbed Brackets - For 2 Slots

For 8 Series (Slot Width 10mm) Aluminum Extrusions




Extruded Brackets - For 2 Slots


For 8 Series (Slot Width 10mm) Aluminum Extrusions




MMaterial: A6N01SS-T5

Surface Treatment: Anodize







Part	Mass	Applica	able S	Screw, T N	lut	Allowable Load	Unit	Price	Volume Discount Rate
Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99	pc(s).	100~200
HBLFSD8	89	CBM8-20	4	HNTT8-8	4	3087			
HBLFSDK8	09	GDIVIO-20	4	пічтто-о	4	3007			





Alterations	Code	Spec.	Applicable Bracket
		Adds taps on a bracket for cover mounting.	HBLFTD8
Mounting Hole	c	(M5 on Both Sides) (Mounting Screw HCBM on P.754)	HBLFUD8
Alteration for Cover			HBLFSD8
		Tapped Hole Position	HBLFSDK8



Alterations	Code	Spec.	Applicable Bracket
	SET SST (Stainless Steel) SEU (Pre-Assembly Insertion)	Applicable screws and nuts for fixing the brackets on extrusions come in a set. (Adds to the bracket price.) (Ex.) When HBLFSD8 is specified:	HBLFTD8
Applicable Screws and Nuts Set	Spring Nuts SSU Pre-Assembly Insertion Spring Nuts	Code Screw Nut SET CBM8-20 HNTT8-8 SST SC88-20 HNTT8N-8 SSU CBM8-20 HNTU8-8 SSU SC88-20 HNTU8-8 SSP SC88-20 SHNTU8-8 SSP SC88-20 SHNTP8-8 SSP SC88-20 SHNTP8-8 SEC (HCBST8-24 HNTT8-8 *When specifying other than HBLFSD8, check for the applicable screws and nuts.	HBLFSD8 HBLFSDK8



4 HNTT8-8 154 CBM8-20 (Black Anodize) (Clear Coating

Both sides and screw holes of NBLTD8 is not anodized.


* For repairing black anodizing, refer to P.846.

Features: Numbers of screws are the same as HBLTD8. Extrusions can be connected more securely



| Mass | Applicable Screw, T Nut | Allowable Load | Unit Price | Volume Discount Rate | (g) | Screw | Quantity | T Nut | Quantity | N | N | 1 - 99 pc(s). | 100-200 380 CBM8-25 4 HNTT8-8 4 3920


Features: Brackets for 2-slot extrusions with 4 mounting holes on one side can connect extrusions more securely.



					FUILITIE DISCOURT TISTE			
Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99 pc(s).	100~200
IBLTDW8	267	CBM8-20	8	HNTT8-8	8	4410		

Features: Numbers of screws are the same as HBLTDW8. Extrusions can be connected more securely.






Part	Mass	Applicab	le S	Screw, T	Nut	Allowable Load	Unit	Price	Volume Discount Rate
Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99	pc(s).	100~200
NBLUDW8	332	CBM8-15	4	HNTT8-8	8	5586			
NDLUDWO	332	CBM8-25	4	ПИ110-0	0	3300			
HBLUDW8	332	CBM8-15	4	HNTT8-8	8	5586			
HBEODWO	332	CBM8-25	4	11111110-0	0	3300			





Alterations	Code	Spec.	Applicable Bracket
		Adds taps on a bracket for cover	NBLTD8
		mounting.	HBLTD8
Mounting Hole		(M5 on Both Sides, Depth 15mm) (Mounting Screw HCBM on P.754)	CHBLTD8
Alteration	С	(S)	HBLTDW8
for Cover			HBLUD8
			NBLUDW8
		Tapped Hole Position	HBLUDW8



Spec.

Screws for black anodized brackets are HCBMTB (Trivalent Chromate Black) on P.751. • Included Screw is not RoHS compliant when -SET, -SEU or -SEP other than black anodized brackets is specified.